SIDE BY SIDE COMBINATIONS

SBSes 7253









SIDE BY SIDE COMBINATION SBSes 7253




Bio Fresh

Smart **Steel**







Whilst every effort is made to ensure all specifications and information in this flyer are correct at time of printing, Andi-Co Australia Pty. Ltd. reserve the right to make changes without notification. Where actual appliance measurements, specifications and ratings are crucial, we recommend that the actual appliance installation instructions that accompany each appliance be checked. Andi-Co Australia will not be liable for any loss.

Model	SBSes	7253*
*Side-by-Sides comprised of two models	SGNes 3010	SKBes 4210
Type I Finish	FS I SmartSteel ^o	FS I SmartSteel ^o
Energy consumption (kWh/yr) I Star rating	310kWh I 3.5	252kWh I 3.0
Compressors	1	1
Total capacity litres (L) - Gross I Net	304 261	403 364
Refrigerator gross (L) Refrigerator net (L)	-	277 247
Freezer gross (L) I Freezer net (L)	304 261	-
BioFresh gross (L) I BioFresh net (L)	-	126 117
MagicEye control system I Display	SoftTouch I LCD	SoftTouch I LCD
Child proof setting for display & temp.	•	•
LED standard lighting	•	•
SlimLine handle - integrated opening device	•	•
Door open warning signal	•	•
Temperature alarm	•	-
Malfunction warning signal	•	•
Refrigerator Features		
BioFresh drawers on telescopic rails	N/A	3
SuperCool	N/A	•
GlassLine shelves	N/A	•
Elegant holding columns	N/A	•
Removable VarioBoxes	N/A	•
Automatic refrigerator defrosting	N/A	•
Freezer Features		
Freezer defrosting	Frost Free	N/A
FrostSafe system with transparent drawers	•	N/A
Freezer drawers I Ice cube drawer	8 -	N/A
SuperFrost	•	N/A
24hr freezing capacity (kg)	20	N/A
Cold storage accumulators	2	N/A
Technical Information		
Default hinge	Left	Right
Voltage (V) I Rated Current (A)	220-240 1.3	220-240 1.2
Made in	Bulgaria	Bulgaria

KEY: FS = Freestanding, N/A = Not Applicable, $^{\circ}$ = SmartSteel is only on doors, * = Freestanding side by sides consist of two Liebherr models. These models **can** be purchased separately. Cavity clearance for freestanding units please allow min. 50 mm above the unit if there is no ventilation cut-out.