

# GKv 6460

## ProfiLine



|   |                                 |
|---|---------------------------------|
| Gross/net capacity                              | 664/491 litre                   |
| Ext. dimensions in mm (w/d/h)                   | 747/791/2064                    |
| Int. dimensions in mm (w/d/h)                   | 650/581/1710                    |
| Energy consumption in 365 days / 24 hours (kWh) | 706 / 1.933                     |
| Ambient temperature range                       | +10°C to +43°C <sup>1</sup>     |
| Refrigerant                                     | R 600a                          |
| Connection Rating                               | 2.0 A / 90 W                    |
| Frequency / Voltage                             | 50 Hz / 220-240 V~              |
| Cooling system                                  | forced-air                      |
| Defrosting                                      | automatic                       |
| Temperature range                               | +1°C to +15°C                   |
| Gastronorm                                      | 650 x 530 mm                    |
| Housing material/colour                         | stainless steel/stainless steel |
| Door material                                   | Stainless steel                 |
| Liner Material                                  | moulded polystyrol white        |
| Type of Control                                 | electronic controller           |
| Temperature display                             | external digital                |
| Fault: warning signal                           | visual and audible              |
| Adjustable Shelving                             | 6                               |
| Height of adjustable legs                       | 150 - 180 mm                    |
| Lock  | fitted                          |
| Self-closing door                               | yes                             |
| Door hinges                                     | right, reversible               |
| Insulation                                      | 50 mm                           |
| Gross/net weight                                | 104/95 kg                       |
| EAN-Nr.   | 9005382196434                   |

<sup>1</sup> Indicates the ambient temperature at which the device can be operated safely.

